

21423 Winsen (Luhe) - Germany


Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01033

Description: BASIC TOUCH

Latex examination glove white, non sterile, powder free





PRODUCT DESCRIP	TION						
material	☑ Latex	☐ Nitrile	□ Vinyl	☐ Vinyl-Nitrile- mixture	Polyethy-lene (PE)	☐ TPE	☐ cotton
colour	☑ white	☐ blue	black	☐ mint	☐ purple	☐ mix	apple-green
characteristics	☐ prepowdered	powderfree	☐ sterile	non sterile	☑ ambidex-	☐ fits hand-	☐ biodgra-
					trous	specific	dable
surface	☑ full textured	finger textured	not textured	embossed	polymer coate	d inside	
SIZES							
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA	AIRS						
PPE-Regulation	☐ Category I	☐ Category II	Category III	☐ no PPE-article			
(EU) 2016/425							
MD-Regulation	☑ Class I	Class II a	☐ Class III	□ sterile	☐ measuring	no medical	CE
(EU) 2017/745					function	device	
Food Contact	☑ acidic foods	☑ aqueous		☑ alcoholic	☑ dry foods	☐ not approved	
(EG) 1935/2004		foods		foods		for food-	52"
						contact	<i></i> .
CTANDADDICATION		l		J	l		l
STANDARDISATION							
EN 388 Mechanical	abrasion	blade cut	tear resistance	puncture	blade cut	impact test	
Risks	resistance	resistance		resistance	resistance		
Level	not applicable	Coupe-Test			TDM-Test		1
Level	not applicable	Coupe-Test	code letter	level		degradation	
EN 374-1	chemical		code letter	level	permeation time	degradation	ISO 374-1/Type B
	chemical Sodium hydroxide	40%	К	6	permeation time > 480 min	-62,5 %	ISO 374-1/Type B
EN 374-1 Chemical Risks	chemical Sodium hydroxide Hydrogen Peroxide	40% e 30%	K P	6 2	permeation time > 480 min > 30 min	-62,5 % -31,9 %	ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4	chemical Sodium hydroxide	40% e 30%	К	6	permeation time > 480 min	-62,5 %	ISO 374-1/Type B
EN 374-1 Chemical Risks	chemical Sodium hydroxide Hydrogen Peroxide	40% e 30%	K P	6 2	permeation time > 480 min > 30 min	-62,5 % -31,9 %	ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4 Degradation	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%	40% = 30% 6	K P T	6 2 4	permeation time	-62,5 % -31,9 % -87,4 %	KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%	40% = 30% 6	K P T	6 2 4	permeation time > 480 min > 30 min	-62,5 % -31,9 % -87,4 %	KPT 8N 150 374-3-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%	40% = 30% 6	K P T	6 2 4	permeation time	-62,5 % -31,9 % -87,4 %	KPT B) 150 315-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a	40% e 30% 6 gainst microorganis	K P T T Sms (viral, bacteria a	6 2 4	permeation time	-62,5 % -31,9 % -87,4 %	KPT 8N 150 334-32016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a	40% = 30% 6	K P T T Sms (viral, bacteria a	6 2 4	permeation time	-62,5 % -31,9 % -87,4 %	KPT EN 150 274-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a	40% e 30% 6 gainst microorganis	K P T T Sms (viral, bacteria a	6 2 4	permeation time	-62,5 % -31,9 % -87,4 %	KPT BN 150 3345-52016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a	40% 2 30% 6 gainst microorganis	K P T T Sms (viral, bacteria a cording to EN 420	6 2 4 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT EN 150 374-5-2016 VIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a	40% 2 30% 6 gainst microorganis	K P T T Sms (viral, bacteria a cording to EN 420	6 2 4	permeation time	-62,5 % -31,9 % -87,4 %	KPT EN 150 274-5-2016 VIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a	40% 2 30% 6 gainst microorganis	K P T T Sms (viral, bacteria a cording to EN 420	6 2 4 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT EN 150 374-5-2016 VIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for single use	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a The glove meets th	40% 2 30% 6 gainst microorganis ne requirements acc	K P T T Sms (viral, bacteria a cording to EN 420 cording to EN 455-1	6 2 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT EN 150 284-52916 VIRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for single use EN 455-1	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a The glove meets th The glove meets th	40% 2 30% 6 gainst microorganis ne requirements according requirements according to the control of the control	K P T T Sms (viral, bacteria a cording to EN 420 cording to EN 455-1	6 2 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT KPT KPT KPT KPT KPT KPT KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for single use	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a The glove meets th	40% 2 30% 6 gainst microorganis ne requirements according requirements according to the control of the control	K P T T Sms (viral, bacteria a cording to EN 420 cording to EN 455-1	6 2 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT EN 150 JP4-32916 VIRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a The glove meets th The glove meets th The glove has an A general Inspection	40% 2 30% 6 gainst microorganis ne requirements according requirements according to the control of the control	K P T T Sms (viral, bacteria a cording to EN 420 cording to EN 455-1	6 2 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT KPT KPT KPT KPT KPT KPT KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a The glove meets th The glove meets th	40% 2 30% 6 gainst microorganis ne requirements according requirements according to the control of the control	K P T T Sms (viral, bacteria a cording to EN 420 cording to EN 455-1	6 2 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT KPT KPT KPT KPT KPT KPT KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN 420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	chemical Sodium hydroxide Hydrogen Peroxide Formaldehyde 37% The glove is tight a The glove meets th The glove meets th The glove has an A general Inspection	40% 2 30% 6 gainst microorganis ne requirements according requirements according to the control of the control	K P T T Sms (viral, bacteria a cording to EN 420 cording to EN 455-1	6 2 4 and fungi). Test acco	permeation time	-62,5 % -31,9 % -87,4 %	KPT KPT KPT KPT KPT KPT KPT KPT



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01033

Description: BASIC TOUCH

Latex examination glove


white, non sterile, powder free

LOGISTIC DATA S		
generell information	n	
material	carton	
pieces per subpacking		100
GTIN subpacking size XS		4044941005201
GTIN subpacking size S		4044941005218
GTIN subpacking size M		4044941005255
GTIN subpacking size L		4044941005232
GTIN subpacking siz	4044941005249	
GTIN subpacking siz	-	
GTIN subpacking size XXXL		-
PZN subpacking size XS		15577768
PZN subpacking size S		15577751
PZN subpacking size M		15577745
PZN subpacking size	L	15577739
PZN subpacking size XL		15577722
PZN subpacking size XXL		=
PZN subpacking size XXXL		-
measures & size		
length		220 mm
width		115 mm
heigth	67 mm	
weights		
size	net weight	gross weight
XS	400 g	460 g
S	450 g	510 g
М	500 g	560 g
L	550 g	610 g
XL 600 g		660 g
XXL	=	-
XXXL -		-

LOGISTIC DATA	PALETTE	
general information	on	
kind of palett		euro-palette
measures & size		
cartons per layer	9	
layers per palette		7
heigth of the palette		173 cm
weights		
size	net weight	gross weight
XS	321 g	346 g
S	353 g	378 g
M	384 g	409 g
L	416 g	441 g
XL	447 g	472 g
XXL	=	-
XXXL	-	-



LOGISTIC DATA	OUTER PACKING	
generell informati		
material		carton
subpackings per o	uter packing	10
GTIN outer packing	g size XS	4044941005256
GTIN outer packing	4044941005263	
GTIN outer packing	4044941005270	
GTIN outer packing	4044941005287	
GTIN outer packing	4044941005294	
GTIN outer packing	-	
GTIN outer packing	-	
PZN outer packing	size XS	-
PZN outer packing	size S	-
PZN outer packing	size M	-
PZN outer packing	size L	-
PZN outer packing	size XL	-
PZN outer packing	size XXL	-
PZN outer packing	size XXXL	-
measures & size		
length	343 mm	
width		233 mm
heigth		225 mm
weights		
size	net weight	gross weight
XS	4.600 g	5.100 g
S	5.100 g	5.600 g
M	5.600 g	6.100 g
L	6.100 g	6.600 g
XL 6.600 g		7.100 g
XXL -		-
XXXL	-	-





21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01033

Description: BASIC TOUCH

Latex examination glove

white, non sterile, powder free



WARNINGS AND SAFETY INFORMATION

storage /	expiry
date	

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

disposal

Used gloves must be disposed of after contact with chemicals in accordance with the disposal regulations for the chemical and the regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

warnings/ allergy information

Protective gloves are intended for single use only.

This product contains dithiocarbamates and natural latex, which can trigger allergic reactions, including anaphylactic reactions

donning and doffing instructions











rev-no.: 8

date 09.09.2024

changes and errors excepted